

ALUMINUM RIGID SPECIAL RADIUS 45° SWEEPS

Description:


Aluminum elbows are to be installed on conduit raceways for the underground stub-ups, and interconnection of conduit runs and other fittings.

Features:

- Fabricated from UL Listed Aluminum Conduit
- Each end threaded (NPT)
- Each end fitted with protective end cap

Certifications and Compliances:

- Made in the USA
- A.R.R.A. Available
- ANSI C80.5
- WW-C-540c
- ASTM B221
- UL File Number E230584



Options:

Available in any degree of bend from 5° to 90°, and special radius

12" - 15" - 18"															
Radius															
A 12 Inch				15 Inch				18 Inch							
Size	Item Number	B	C	T	Wt.	Item Number	B	C	T	Wt.	Item Number	B	C	T	Wt.
1"	AR1012SW45	24	10	10	1.30	AR1015SW45	26	11	10	1.50	AR1018SW45	30	12.5	11	1.50
1-1/4"	AR1212SW45	24	10	10	1.90	AR1215SW45	26	11	10	1.90	AR1218SW45	30	12.5	11	2.20
1-1/2"	AR1512SW45	24	10	10	2.90	AR1515SW45	26	11	10	2.90	AR1518SW45	30	12.5	11	2.90
2"	AR2012SW45	24	10	10	2.80	AR2015SW45	26	11	10	3.10	AR2018SW45	30	12.5	11	3.60
2-1/2"	AR2512SW45	24	10	10	3.90	AR2515SW45	26	11	10	4.60	AR2518SW45	30	12.5	11	5.40
3"						AR3015SW45	26	11	10	6.130	AR3018SW45	30	12.5	11	7.20

ALUMINUM RIGID SPECIAL RADIUS 45° SWEEPS

24" - 30" - 36"															
Radius															
A 24 Inch					30 Inch					36 Inch					
Size	Item Number	B	C	T	Wt.	Item Number	B	C	T	Wt.	Item Number	B	C	T	Wt.
1"	AR1024SW45	36	15	11	2.30	AR1030SW45	40	17	11	2.50	AR1036SW45	44	18.5	11	2.70
1-1/4"	AR1224SW45	36	15	11	3.00	AR1230SW45	40	17	11	3.20	AR1236SW45	44	18.5	11	3.20
1-1/2"	AR1524SW45	36	15	11	3.00	AR1530SW45	40	17	11	3.40	AR1536SW45	44	18.5	11	3.90
2"	AR2024SW45	36	15	11	4.30	AR2030SW45	40	17	11	5.00	AR2036SW45	44	18.5	11	5.00
2-1/2"	AR2524SW45	36	15	11	5.40	AR2530SW45	40	17	11	8.00	AR2536SW45	44	18.5	11	7.90
3"	AR3024SW45	36	15	11	9.00	AR3030SW45	40	17	11	9.70	AR3036SW45	44	18.5	11	10.00
3-1/2"	AR3524SW45	36	15	11	10.00	AR3530SW45	40	17	11	10.50	AR3536SW45	44	18.5	11	12.60
4"	AR4024SW45	36	15	11	12.00	AR4030SW45	40	17	11	14.80	AR4036SW45	44	18.5	11	15.00
5"						AR5030SW45	40	17	11	19.00	AR5036SW45	44	18.5	11	21.60
6"											AR6036SW45	44	18.5	11	43.50

48" - 60"										
Radius										
A 48 Inch					60 Inch					
Size	Item Number	B	C	T	Wt.	Item Number	B	C	T	Wt.
1"	AR1048SW45	54.5	22.5	12	3.00	AR1060SW45	62	26	12	3.40
1-1/4"	AR1248SW45	54.5	22.5	12	4.00	AR1260SW45	62	26	12	4.60
1-1/2"	AR1548SW45	54.5	22.5	12	5.00	AR1560SW45	62	26	12	5.70
2"	AR2048SW45	54.5	22.5	12	6.50	AR2060SW45	62	26	12	7.40
2-1/2"	AR2548SW45	54.5	22.5	12	10.40	AR2560SW45	62	26	12	11.90
3"	AR3048SW45	54.5	22.5	12	14.00	AR3060SW45	62	26	12	16.00
3-1/2"	AR3548SW45	54.5	22.5	12	16.00	AR3560SW45	62	26	12	18.30
4"	AR4048SW45	54.5	22.5	12	19.00	AR4060SW45	62	26	12	21.80
5"	AR5048SW45	54.5	22.5	12	26.00	AR5060SW45	62	26	12	29.80
6"	AR6048SW45	54.5	22.5	12	33.50	AR6060SW45	62	26	12	38.40