

# Calconduit™

Rigid Conduit, Rigid & EMT Fittings

## Aluminum Rigid Factory Elbows - 90°

### Application:

Aluminum Elbows are to be installed on conduit raceways for underground stub-ups, and interconnection of conduit runs and other fittings.

### Features:


- Fabricated from UL Listed Aluminum Conduit
- Each end threaded (NPT)
- Each end fitted with protective end cap

### Certifications and Compliances:

- Made In USA
- A.R.R.A. Available
- ANSI C80.5
- WW-C-540c
- ASTM B221

### Options:

Available in any degree of bend from 5° to 90°, and special radius



90° Elbows				DimensionsCut			
Item Number	Description	Wt. (lbs)	Box Qty.	A	B	T	Cut Length
AR0590EL00	1/2" X 90°	0.30	50	4.0	6.9	2.9	12.0"
AR0790EL00	3/4" X 90°	0.40	50	4.5	7.4	2.9	12.9"
AR1090EL00	1" X 90°	0.70	25	5.8	8.7	3.0	15.0"
AR1290EL00	1-1/4" X 90°	1.10	20	7.3	10.6	3.3	18.0"
AR1590EL00	1-1/2" X 90°	1.50	15	8.3	11.9	3.6	20.3"
AR2090EL00	2" X 90°	2.10	10	9.5	13.8	4.3	23.4"
AR2590EL00	2-1/2" X 90°	5.00	50	10.5	15.8	5.3	27.0"
AR3090EL00	3" X 90°	8.00	35	13.0	18.8	5.8	32.0"
AR3590EL00	3-1/2" X 90°	9.00	35	15.0	21.8	6.8	37.0"
AR4090EL00	4" X 90°	12.00	35	16.0	23.1	7.1	39.3"
AR5090EL00	5" X 90°	24.00	bulk	24.0	35.2	11.2	60.0"
AR6090EL00	6" X 90°	38.00	bulk	30.0	42.6	12.6	72.3"

Calconduit

12021 Woodruff Ave., Downey, CA 90241

Ph: (562) 803.4388 Ph: (800) 225.7473 Fax: (562) 803.4488 | calconduit.com

